




SPIRAALBAND dunwandig ZWART

KEURINGEN ➔		IN- AND OUTDOOR USE	BRUTO Prijs Per 100 Meter					
KENMERKEN ➔	Materiaal : Polyethyleen dunwandig Voor het snel bundelen van kabels en draden Kleur : Zwart							
	<u>Artikelnummer</u>	<u>Ean code</u>	<u>Binnen/Buitendia.</u>	<u>Min/Max wikkel</u>	<u>Zakje</u>	<u>Karton</u>	<u>Stocktype</u>	30.00 €
	12-SPIBZ-DU-035we	5420023932570	2.3 mm x 3.5 mm	3.0 mm x 15 mm	10 Mtr.	100 Mtr.	stock	43.00 €
	12-SPIBZ-DU-050we	5420023932587	3.7 mm x 5.0 mm	4.0 mm x 20 mm	10 Mtr.	100 Mtr.	stock	55.00 €
	12-SPIBZ-DU-080we	5420023932594	6.5 mm x 8.0 mm	7.0 mm x 40 mm	10 Mtr.	100 Mtr.	stock	65.00 €
	12-SPIBZ-DU-100we	5420023932600	8.2 mm x 10 mm	9.0 mm x 50 mm	10 Mtr.	100 Mtr.	stock	70.00 €
	12-SPIBZ-DU-120we	5420023932617	10 mm x 12 mm	11 mm x 70 mm	10 Mtr.	100 Mtr.	stock	75.00 €
	12-SPIBZ-DU-140we	5420023932624	12 mm x 14 mm	13 mm x 80 mm	10 Mtr.	100 Mtr.	stock	166.00 €
	12-SPIBZ-DU-200we	5420023932631	17.6 mm x 20 mm	18 mm x 120 mm	10 Mtr.	100 Mtr.	stock	203.00 €
12-SPIBZ-DU-250we	5420023932648	22.2 mm x 25 mm	23 mm x 150 mm	10 Mtr.	100 Mtr.	stock		

SPIRAALBAND dunwandig NATUREL

KEURINGEN ➔		INDOOR USE	BRUTO Prijs Per 100 Meter					
KENMERKEN ➔	Materiaal : Polyethyleen dunwandig Voor het snel bundelen van kabels en draden Kleur : Naturel							
	<u>Artikelnummer</u>	<u>Ean code</u>	<u>Binnen/Buitendia.</u>	<u>Min/Max wikkel</u>	<u>Zakje</u>	<u>Karton</u>	<u>Stocktype</u>	30.00 €
	12-SPIBN-DU-035we	5420023932495	2.3 mm x 3.5 mm	3.0 mm x 15 mm	10 Mtr.	100 Mtr.	stock	43.00 €
	12-SPIBN-DU-050we	5420023932501	3.7 mm x 5.0 mm	4.0 mm x 20 mm	10 Mtr.	100 Mtr.	stock	55.00 €
	12-SPIBN-DU-080we	5420023932518	6.5 mm x 8.0 mm	7.0 mm x 40 mm	10 Mtr.	100 Mtr.	stock	65.00 €
	12-SPIBN-DU-100we	5420023932525	8.2 mm x 10 mm	9.0 mm x 50 mm	10 Mtr.	100 Mtr.	stock	70.00 €
	12-SPIBN-DU-120we	5420023932532	10 mm x 12 mm	11 mm x 70 mm	10 Mtr.	100 Mtr.	stock	75.00 €
	12-SPIBN-DU-140we	5420023932549	12 mm x 14 mm	13 mm x 80 mm	10 Mtr.	100 Mtr.	stock	166.00 €
	12-SPIBN-DU-200we	5420023932556	17.6 mm x 20 mm	18 mm x 120 mm	10 Mtr.	100 Mtr.	stock	203.00 €
12-SPIBN-DU-250we	5420023932563	22.2 mm x 25 mm	23 mm x 150 mm	10 Mtr.	100 Mtr.	stock		





SBP

non flame retardant - halogen free
operating temperature -50° C to +85° C

SHORT DESCRIPTION

Polyethylene spiral tubing designed for the neat bundling of cables, and to give mechanical protection. Used for ease of application and economy.

STANDARD SIZES

Size mm	Outside diameter	Inside diameter	Wall thickness (nominal)	Bundle capacity	Helix ±1 mm
3.5 x 2.3	3.5	2.3	0.60	3.00 – 15.00	5.00
5.0 x 3.7	5.0	3.7	0.65	4.00 – 20.00	7.00
8.0 x 6.5	8.0	6.5	0.75	7.00 – 40.00	10.00
10.0 x 8.2	10.0	8.2	0.85	9.00 – 50.00	12.00
11.0 x 9.0	11.0	9.0	1.0	10.00 – 50.00	12.00
12.0 x 10.0	12.0	10.0	1.0	11.00 – 70.00	14.00
14.0 x 12.0	14.0	12.0	1.0	13.00 – 80.00	16.00
17.0 x 15.0	17.0	15.0	1.0	16.00 – 90.00	19.00
20.0 x 17.6	20.0	17.6	1.2	18.00 – 120.00	22.00
25.0 x 22.2	25.0	22.2	1.4	23.00 – 150.00	27.00

POSSIBLE ALTERNATIVE SIZES

Size mm	Outside diameter	Inside diameter	Wall thickness (nominal)	Bundle capacity	Helix ±1 mm
3.0 x 1.5	3.0	1.5	0.75	2.00 – 10.00	4.00
6.0 x 4.0	6.0	4.0	1.00	5.00 – 40.00	7.00
9.0 x 7.0	9.0	7.0	1.00	8.00 – 45.00	11.00
11.5 x 8.5	11.5	8.5	1.50	10.00 – 50.00	12.00
12.0 x 9.0	12.0	9.0	1.50	11.00 – 55.00	14.00
15.0 x 12.0	15.0	12.0	1.50	13.00 – 90.00	15.00
19.0 x 16.0	19.0	16.0	1.50	17.00 – 130.00	22.00
24.0 x 20.0	24.0	20.0	2.00	21.00 – 150.00	20.00

CERTIFICATIONS

STOCK COLOURS

black, clear

NON STOCK COLOURS

all others

PROPERTIES

Physical:

tensile strength
ultimate elongation
water absorption
specific gravity (23°C)

Thermal:

Melting point
Peak temperature (short time)
Flammability

Chemical:

chemical resistance

Electrical:

dielectric strength

TEST METHOD

ISO 1183-2

ASTM 635-HB

ASTM D 2671

TYPICAL VALUES

11.45N/mm²
500%
≤0.1% max.
0.922 g / cm³

105°C to 115°C

pass

good

25kV/mm