




STEEKKLEMMEN
VOOR HARDE KABEL
GRIJS NYLON



Push-in Connectors Economy Type

- Housing: Polyamide 6.6
- Flame retardant: UL 94 Class V-2
- Clamp Unit: Tinned steel plate with copper strip and spring steel
- Working temperature: T110 (IEC), 105°C (UL)
- Accepts rigid/solid conductors up to 2,5 mm² / 22~12 AWG
- Rated to 600V max for building wiring and 1000V max for lighting fixtures and signs.
- Compact size design perfect for tight spaces.
- Does not require twisting and taping
- Test slot in the back permits easy testing with a voltage tester
- For use in building distribution and junction boxes
- Can be reused with wire sizes that are larger than the one previously removed

PRT NR.	COLOR	MM²	RATING A	PRODUCT IMAGE	PCS/BAG
PIWC-30GR	3 P	0.5-1.5	24A		500
PIWC-50GR	5 P	0.5-1.5	24A		500
PIWC-80GR	8 P	0.5-1.5	24A		250

Fabric DIN KLEUREN Partnr.	WT ARTIKELNUMMER			Inhoud					
	Industrial pack	WT system	WT system	I-pack		R-pack		S-pack	
	Fabric pack	Retail pack	Small pack	Pack	Carton	Pack	Carton	Pack	Carton
PIWC-30GR	CCNGIZM3P050150-0500	CCNGRWT3P050150-0100	CCNGSWT3P050150-Z005	500	5000	1X100	10X100	6X5	60X5
PIWC-50GR	CCNGIZM5P050150-0500	CCNGRWT5P050150-0100	CCNGSWT5P050150-Z005	500	5000	1X100	10X100	6X5	60X5
PIWC-80GR	CCNGIZM8P050150-0250	CCNGRWT8P050150-0100	CCNGSWT8P050150-Z005	250	2500	1X100	10X100	6X5	60X5