






STEEKKLEMMEN
VOOR HARDE KABEL
POLYCARBONAAT MET KLEURCODE



Push-in Connectors Standard Type

- Housing: Polycarbonate and Polyamide 6.6 (clear items) or Polyamide 6.6
- Flame retardant: UL 94 Class V-0 (clear items) or UL 94-CLASS V-2
- Clamp Unit: Tinned copper or steel plate with copper strip and spring steel
- Working temperature: T110 (IEC), 105°C (UL)
- Accepts solid conductors up to 2,5 mm² / 22~12 AWG
- Rated to 600V max for building wiring and 1000V max for lighting fixtures and signs.
- Compact size design, perfect for tight spaces
- Does not require twisting and taping
- Test slot in the back permits easy testing with a voltage tester
- For use in building distribution and junction boxes
- Can be reused with wire sizes that are larger than the one previously removed

PRT NR.	COLOR	MM ²	RATING A	PC/PA	PRODUCT IMAGE	PCS/BAG
PIWC-2CL	2P	1.0-2.5	24A	PC		500
PIWC-3CL	3P	1.0-2.5	24A	PC		500
PIWC-4CL	4P	1.0-2.5	24A	PC		500
PIWC-5CL	5P	1.0-2.5	24A	PC		500
PIWC-8CL	8P	1.0-2.5	24A	PC		250

Fabric Partnr.	WT ARTIKELNUMMER			Inhoud					
	Industrial pack	WT system	WT system	I-pack		R-pack		S-pack	
	Fabric pack	Retail pack	Small pack	Pack	Carton	Pack	Carton	Pack	Carton
PIWC-2CL	CCPCIWT2P1025RO-0500	CCPCRWT2P1025RO-0050	CCPCSWT2P1025RO-Z005	500	5000	1X50	10X50	6X5	60X5
PIWC-3CL	CCPCIWT3P1025OR-0500	CCPCRWT3P1025OR-0050	CCPCSWT3P1025OR-Z005	500	5000	1X50	10X50	6X5	60X5
PIWC-4CL	CCPCIWT4P1025GE-0500	CCPCRWT4P1025GE-0050	CCPCSWT4P1025GE-Z005	500	5000	1X50	10X50	6X5	60X5
PIWC-5CL	CCPCIWT5P1025GR-0500	CCPCRWT5P1025GS-0050	CCPCSWT5P1025GS-Z005	500	5000	1X50	10X50	6X5	60X5
PIWC-8CL	CCPCIWT8P1025ZW-0250	CCPCRWT8P1025ZW-0025	CCPCSWT8P1025ZW-Z005	250	2500	1X25	10X25	6X5	60X5